

# **SAFETY DATA SHEET**

# 1. Identification

Product identifier	METHYL tert-BUTYL ETHER, VERITAS® ULTIMATE	
Other means of identification		
Product code	5573	
Synonym(s)	TERT-BUTYL METHYL ETHER * 2-Methoxy-2-methylpropane * MTBE * T-BUTYL METHYL ETHER	
Recommended use	professional, scientific and technical activities: other professional, scientific and technical activities	
<b>Recommended restrictions</b>	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Company name	GFS Chemicals, Inc.	
Address	P.O. Box 245	
	Powell	

	Powell	
	OH	
	43065	
	US	
Telephone	Phone	740-881-5501
	Toll Free	800-858-9682
	Fax	740-881-5989
Website	www.gfschemicals.com	
E-mail	service@gfschemicals.com	
Emergency phone number	Emergency Assistance	Chemtrec 800-424-9300

### 2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
OSHA hazard(s)	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Use only outdoors or in a well-ventilated area. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	Eliminate all ignition sources if safe to do so. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. In case of fire: Use appropriate media for extinction.

Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container to an approved incineration plant.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid
Supplemental information	
Hazard statement	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment. These alone may be insufficient to remove static electricity.
3. Composition/information on ingredients	

#### Substances

\_

Hazardous components Chemical name	Common name and synonyms	CAS number	%
METHYL tert-BUTYL ETHER	TERT-BUTYL METHYL ETHER 2-Methoxy-2-methylpropane MTBE T-BUTYL METHYL ETHER	1634-04-4	100

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Move to fresh air. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Most important symptoms/effects, acute and delayed	Irritation of eyes and mucous membranes. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Irritant effects.
Indication of immediate medical attention and special treatment needed	Keep victim under observation. Symptoms may be delayed. Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. By heating and fire, harmful vapors/gases may be formed. Material will float and may ignite on surface of water.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk.

#### 6. Accidental release measures

6. Accidental release measures		
Personal precautions, protective equipment and emergency procedures	Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Wear appropriate personal protective equipment.	
Methods and materials for containment and cleaning up	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Should not be released into the environment.	
	Large Spills: Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. This material and its container must be disposed of as hazardous waste. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basements or confined areas. Clean up in accordance with all applicable regulations.	
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.	
	Never return spills in original containers for re-use. For waste disposal, see section 13 of the MSDS.	
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination. Prevent further leakage or spillage if safe to do so. Do not contaminate water.	
7. Handling and storage		
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Vapors may form explosive mixtures with air. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code". DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with skin. Avoid contact with eyes. Use personal protective equipment as required. Avoid prolonged exposure. Wash hands thoroughly after handling. Avoid release to the environment.	
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in cool place. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a well-ventilated place. Keep container tightly closed. Keep in an area equipped with sprinklers. Keep out of the reach of children. Store in a cool, dry place out of direct sunlight.	

### 8. Exposure controls/personal protection

### Occupational exposure limits

US. ACGIH Threshold Limit Values			
Material	Туре	Value	
METHYL tert-BUTYL ETHER (CAS 1634-04-4)	TWA	50 ppm	
Biological limit values	No biological exposure limits noted	for the ingredient(s).	

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Provide eyewash station.
Individual protection measure	es, such as personal protective equipment
Eye/face protection	Avoid contact with eyes. Wear eye/face protection.
Skin protection	
Hand protection	Wear protective gloves.
Other	Wear suitable protective clothing. Wear protective gloves.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	Not available.
General hygiene considerations	When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Appearance	Clear.
Physical state	Liquid.
Form	Liquid.
Color	Colorless.
Odor	Ether-like.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	-163.5 °F (-108.6 °C)
Initial boiling point and boiling range	131.36 °F (55.2 °C)
Flash point	-18.40 °F (-28.00 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or ex	cplosive limits
Flammability limit - lower (%)	> 1.6 %
Flammability limit - upper (%)	< 15.1 %
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	33.33 kPa at 25 °C
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	42 g/l
Partition coefficient (n-octanol/water)	0.9
Auto-ignition temperature	707 °F (375 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.74 g/cm3 estimated
Flammability class	Flammable IB estimated
Flash point class	Flammable IB
Molecular formula	C5-H12-O
Molecular weight	88.15 g/mol
Percent volatile	100 %
Specific gravity	0.7405 at 20 °C
VOC (Weight %)	100 %

### 10. Stability and reactivity

Reactivity	Not available.
Chemical stability	Risk of explosion. May form explosive peroxides.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
Incompatible materials	Oxidizing agents. Strong acids.
Hazardous decomposition products	Irritants. Carbon oxides.

### **11.** Toxicological information

#### Information on likely routes of exposure

Ingestion	May be fatal if swallowed and enters airways.
Inhalation	May be fatal if swallowed and enters airways. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause irritation to the respiratory system.
Skin contact	Not available.
Eye contact	Causes eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Irritant effects. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

#### Information on toxicological effects

Acute toxicity	May be fatal if swallowed and end	nters airways.
Product	Species	Test Results
METHYL tert-BUTYL ETHER	R (CAS 1634-04-4)	
Acute		
Inhalation		
LC50	Rat	85 mg/l, 4 Hours
Oral		
LD50	Rat	4 ml/kg
Other		
LD50	Rabbit	> 10 ml/kg
		> 10 ml/kg

 $\ast$  Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes eye irritation.		
Respiratory sensitization	Due to lack of data the classification is not possible.		
Skin sensitization	Based on available data, the classification criteria are not met.		
Germ cell mutagenicity	Based on available data, the classification criteria are not met.		
Carcinogenicity	Suspected of causing cancer.		
IARC Monographs. Overall	Evaluation of Carcinogenicity		
METHYL tert-BUTYL ETHE	R (CAS 1634-04-4) 3 Not classifiable as to carcinogenicity to humans.		
Reproductive toxicity	Based on available data, the classification criteria are not met.		
Specific target organ toxicity - single exposure	Respiratory tract irritation. Narcotic effects.		
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.		
Aspiration hazard	May be fatal if swallowed and enters airways.		
Chronic effects	Prolonged inhalation may be harmful.		

### **12. Ecological information**

Ecotoxicity

Contains a substance which causes risk of hazardous effects to the environment.

Product		Species	Test Results
METHYL tert-BUTYL ETHER (	CAS 1634-04-4)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	672 mg/l, 96 hours
* Estimates for product may l	be based on add	litional component data not shown.	
Persistence and degradability	No data is ava	ailable on the degradability of this product.	
Bioaccumulative potential	Not available.		
Partition coefficient n-oct 0.94	anol / water (	log Kow)	
Mobility in soil	Not available.		
Other adverse effects	Not available.		
13. Disposal consideration	ons		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.		
Local disposal regulations	Not available.		
Hazardous waste code	D001: Waste Flammable material with a flash point $<$ 140 F		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
Contaminated packaging		ners should be taken to an approved waste I containers may retain product residue, fo	
14. Transport informatio	n		
Dot			

DOT	
UN number	UN2398
UN proper shipping name	Methyl tert-butyl ether
Transport hazard class(es)	3
Subsidary class(es)	Not available.
Packing group	II
Special precautions for	Read safety instructions, SDS and emergency procedures before handling.
user	
Labels required	3
Special provisions	IB2, T7, TP1
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242
ΙΑΤΑ	
UN number	UN2398
UN proper shipping name	Methyl tert-butyl ether
Transport hazard class(es)	3
Subsidary class(es)	-
Packaging group	II
Environmental hazards	No
Labels required	Not available.
ERG Code	3L
Special precautions for	Not available.
user	
IMDG	
UN number	UN2398
UN proper shipping name	METHYL tert-BUTYL ETHER
Transport hazard class(es)	3
Subsidary class(es)	-
Packaging group	II
Environmental hazards	
Marine pollutant	No
Labels required	Not available.
Material name: METHYL tert-BUTYL ET	HER, VERITAS® ULTIMATE

EmS Special precautions for user F-E, S-D Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code DOT

No information available.



### 15. Regulatory information

15. Regulatory information	on		
US federal regulations	All components are on the	U.S. EPA TSCA Inventory List.	
TSCA Section 12(b) Expor	t Notification (40 CFR 707	, Subpt. D)	
Not regulated.			
US. OSHA Specifically Reg	ulated Substances (29 CFI	₹ 1910.1001-1050)	
Not on regulatory list.			
METHYL tert-BUTYL ETH	i i	LISTED	
Superfund Amendments and F		6 (SARA)	
Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No		
SARA 302 Extremely hazardous substance	No		
SARA 311/312 Hazardous chemical	No		
Other federal regulations			
Clean Air Act (CAA) Sectio	n 112 Hazardous Air Pollu	tants (HAPs) List	
METHYL tert-BUTYL ETH	· · · · · · · · · · · · · · · · · · ·		
• •	n 112(r) Accidental Releas	se Prevention (40 CFR 68.130)	
Not regulated.			
Safe Drinking Water Act (SDWA)	Contaminate candidate list Monitoring		
Drug Enforcement Admini Chemical Code Number	stration (DEA). List 2, Esse	ential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2	) and
Not listed.			
Drug Enforcement Admini	stration (DEA). List 1 & 2	Exempt Chemical Mixtures (21 CFR 1310.12(c))	
Not regulated.			
DEA Exempt Chemical Mix	tures Code Number		
Not regulated.			
Material name: METHYL tert-BUTYL E	THER, VERITAS® ULTIMATE		SDS

Not regulated.

#### Food and Drug Administration (FDA) US state regulations

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

# US. Massachusetts RTK - Substance List

METHYL tert-BUTYL ETHER (CAS 1634-04-4)

US. New Jersey Worker and Community Right-to-Know Act

METHYL tert-BUTYL ETHER (CAS 1634-04-4) 500 lbs

US. Pennsylvania RTK - Hazardous Substances

METHYL tert-BUTYL ETHER (CAS 1634-04-4)

# US. Rhode Island RTK

METHYL tert-BUTYL ETHER (CAS 1634-04-4)

### US. California Proposition 65

#### US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance Not listed.

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*Δ "Yes" indicates this product o	omplies with the inventory requirements administered by the governing country(s)	

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

### 16. Other information, including date of preparation or last revision

Issue date	November-08-2013
Version #	01
Further information	Not available.
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.