

# SAFETY DATA SHEET

# Identification

1. Identification			
Product identifier	ISOPROPYL ALCOHOL, R	EAGENT (ACS)	
Other means of identification			
Product code	2294		
CAS number	67-63-0		
Synonyms	ISOPROPANOL * 2-PROPAN	OL	
Recommended use	solvent technical function of professional, scientific and to		ssional, scientific and technical activities: other
<b>Recommended restrictions</b>	None known.		
Manufacturer/Importer/Suppl Manufacturer	ier/Distributor informatio	n	
Company name Address	GFS Chemicals, Inc. 800 Kaderly Drive Columbus, OH 43228 United States		
Telephone	Phone Toll Free Fax	740-881-5501 800-858-9682 740-881-5989	
Website E-mail	www.gfschemicals.com service@gfschemicals.com		
Emergency phone number	Emergency Assistance	Chemtrec 800-42	24-9300
2. Hazard(s) identification	n		
Physical hazards	Flammable liquids		Category 2
Health hazards	Serious eye damage/eye irri	tation	Category 2
	Specific target organ toxicity	, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified.		
OSHA defined hazards	Not classified.		
Label elements			
Signal word	Danger		
Hazard statement	Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness.		
Precautionary statement			
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection.		
Response			ontaminated clothing. Rinse skin with water/shower.

None.

Storage

Disposal

Hazard(s) not otherwise

**Supplemental information** 

classified (HNOC)

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

applicable laws and regulations, and product characteristics at time of disposal.

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with

Static accumulating flammable liquid can become electrostatically charged even in bonded and

grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

### 3. Composition/information on ingredients

#### Substances

Chemical name	Common name and synonyms	CAS number	%
ISOPROPYL ALCOHOL	ISOPROPANOL	67-63-0	100
	2-PROPANOL		

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Designates that a specific chemic	and that is a second ge of composition has been while a do a trade second
4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Do not use mouth-to-mouth method if victim ingested the substance. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	5
Suitable extinguishing media	Water. Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods General fire hazards	Use standard firefighting procedures and consider the hazards of other involved materials. Highly flammable liquid and vapor.
6. Accidental release me	asures
Personal precautions,	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Clean contaminated surface thoroughly. This product is miscible in water. Should not be released into the environment. Clean up in accordance with all applicable regulations.
	Large Spills: Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. After removal flush contaminated area thoroughly with water. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).
8. Exposure controls/pers	sonal protection
Occupational exposure limits	
	the only constituents of the product which have a PEL, TLV or other recommended exposure limit. ents have no known exposure limits.
US. OSHA Table Z-1 Limits Material	for Air Contaminants (29 CFR 1910.1000) Type Value

туре	value	
PEL	980 mg/m3	
	400 ppm	
S		
Туре	Value	
STEL	400 ppm	
TWA	200 ppm	
mical Hazards		
Туре	Value	
STEL	1225 mg/m3	
	500 ppm	
	PEL PEL STEL TWA mical Hazards Type	PEL 980 mg/m3 400 ppm <b>Type Value</b> STEL 400 ppm TWA 200 ppm <b>mical Hazards</b> <b>Type Value</b> 1225 mg/m3

Material		Гуре		alue
	T	ΓWA	98	0 mg/m3
			40	0 ppm
ological limit values ACGIH Biological Exposure Material V	e Indices alue	Determinant	Specimen	Sampling Time
ISOPROPYL ALCOHOL (CAS 4 67-63-0)	) mg/l	Acetone	Urine	*
* - For sampling details, pleas	e see the source	document.		
opropriate engineering ontrols	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.			
dividual protection measure Eye/face protection		onal protective equip es are recommended.	oment	
Skin protection Hand protection	Wear appropria	te chemical resistant gl	oves.	
Other		J		
Respiratory protection	Wear appropriate chemical resistant clothing. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor cartridge.			
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.			
eneral hygiene onsiderations	When using do not smoke. Always observe good personal hygiene measures, such as washing at handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			
. Physical and chemical	properties			
opearance	Clear.			
Physical state	Liquid.			
Form	Liquid.			
Color	Colorless.			
dor	Alcoholic.			
dor threshold	Not available.			
4	Not available.			
elting point/freezing point	-127.3 °F (-88.5	5 °C)		
iitial boiling point and biling range	180.5 °F (82.5 °C) 101.325 kPa			
ash point	53.6 °F (12.0 °C 75.0 °F (23.9 °C			
aporation rate	Not available.			
ammability (solid, gas)	Not applicable.			
oper/lower flammability or e Flammability limit - lower (%)	-			
Flammability limit - upper (%)	12 %			
Explosive limit - lower (%)	Not available.			
Explosive limit - upper (%)	Not available.			
apor pressure	6.05 kPa (77 °F	<sup>:</sup> (25 °C))		

Solubility(ies)	
Solubility (water)	Miscible
Partition coefficient (n-octanol/water)	0.05
Auto-ignition temperature	750.2 °F (399 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.78 g/cm3 estimated at 20 °C
Dynamic viscosity	2.1 mPa.s (77 °F (25 °C))
Explosive properties	Not explosive.
Flammability class	Flammable IB estimated
Flash point class	Flammable IB
Heat of combustion (NFPA 30B)	27.4 kJ/g
Kinematic viscosity	2.676 mm <sup>2</sup> /s estimated
Molecular formula	СЗ-Н8-О
Molecular weight	60.10 g/mol
Oxidizing properties	Not oxidizing.
Percent volatile	100 %
Specific gravity	0.79 at 20 °C
Surface tension	20.93 mN/m (77 °F (25 °C))
VOC	100 %

# 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Risk of ignition. Stable at normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Chlorine. Isocyanates.
Hazardous decomposition products	May include oxides of carbon.

# 11. Toxicological information

#### Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

#### Information on toxicological effects

Acute toxicity	Not known.	
Product	Species	Test Results
ISOPROPYL ALCOHOL (C/	AS 67-63-0)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	5030 - 7900 mg/kg
		12800 mg/kg
Oral		
LD50	Dog	4797 mg/kg
	Mouse	3600 mg/kg

Product	Species		Test Results	
	Rabbit		8000 mg/kg	
			6410 mg/kg	
	Rat		4700 - 5800 mg/kg	
			5045 mg/kg	
			4.7 g/kg	
Other				
LD50	Mouse		1509 mg/kg	
	Rat		1099 mg/kg	
Skin corrosion/irritation	Prolonged sk	kin contact may cause temporary irritati	on.	
Serious eye damage/eye irritation		ous eye irritation.		
Respiratory or skin sensitizatio				
Respiratory sensitization		atory sensitizer.	i e e	
Skin sensitization Germ cell mutagenicity	-	is not expected to cause skin sensitization in the sensitization indicate product or any composition of the sensitive s	nents present at greater than 0.1% are	
	mutagenic o	r genotoxic.	ients present at greater than 0.1% are	
Carcinogenicity		ble as to carcinogenicity to humans.		
IARC Monographs. Overall Not listed.				
	ed Substance	es (29 CFR 1910.1001-1052)		
Not regulated. US. National Toxicology Pr Not listed.	ogram (NTP)	) Report on Carcinogens		
Reproductive toxicity	This product	is not expected to cause reproductive	or developmental effects.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.			
Specific target organ toxicity - repeated exposure	Not classified.			
Aspiration hazard	Not an aspira	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be harmful.			
12. Ecological informatio	n			
Ecotoxicity	The product		ardous. However, this does not exclude the armful or damaging effect on the environment	
Product	. ,	Species	Test Results	
ISOPROPYL ALCOHOL (CAS 6	7-63-0)			
Aquatic				
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours	
	No data is av	vailable on the degradability of this subs	stance.	
Bioaccumulative potential Partition coefficient n-octa	anol / water	(log Kow)		
0.05 <b>Mobility in soil</b>	No data avai	ilable.		
Other adverse effects			hich have a photochemical ozone creation	
13. Disposal consideration	•			
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.			
Local disposal regulations	Dispose in a	ccordance with all applicable regulation	s.	
Hazardous waste code			<140 F etween the user, the producer and the waste	

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport information

DOT	
υυι	

DOT	
UN number	UN1219
UN proper shipping name	Isopropanol or Isopropyl alcohol
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for	Read safety instructions, SDS and emergency procedures before handling.
user	······································
Special provisions	IB2, T4, TP1
Packaging exceptions	4b, 150
Packaging non bulk	202
Packaging bulk	242
ΙΑΤΑ	
UN number	UN1219
UN proper shipping name	Isopropanol
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	П
Environmental hazards	No.
ERG Code	3L
Special precautions for	Read safety instructions, SDS and emergency procedures before handling.
user	
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1219
UN proper shipping name	ISOPROPANOL (ISOPROPYL ALCOHOL)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for	Read safety instructions, SDS and emergency procedures before handling.
user	
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78	
and the IBC Code	
DOT	

3



# 15. Regulatory information

15. Regulatory Informati	ON		
US federal regulations	This product is a "Hazard 29 CFR 1910.1200.	lous Chemical" as defined by the OSHA Haza	ard Communication Standard,
Toxic Substances Control Act (TSCA)	This substance is on the	TSCA 8(b) inventory and is designated "activ	ve".
TSCA Section 12(b) Ex	port Notification (40 CF	R 707, Subpt. D)	
Not regulated.			
F - Highly flammable			
<b>CERCLA Hazardous Substa</b>	nce List (40 CFR 302.4)		
Not listed. SARA 304 Emergency relea	ase notification		
Not regulated. OSHA Specifically Regulat	ed Substances (29 CFR	1910.1001-1052)	
Not regulated.			
Superfund Amendments and R		986 (SARA)	
SARA 302 Extremely haza	rdous substance		
Not listed.			
SARA 311/312 Hazardous chemical	Yes		
Classified hazard categories	Flammable (gases, aeros Serious eye damage or e Specific target organ toxi Hazard not otherwise class	ye irritation city (single or repeated exposure)	
SARA 313 (TRI reporting) Not regulated.			
Other federal regulations			
Clean Air Act (CAA) Sectio	n 112 Hazardous Air Pol	llutants (HAPs) List	
Not regulated. Clean Air Act (CAA) Sectio	n 112(r) Accidental Rele	ease Prevention (40 CFR 68.130)	
Not regulated.			
Safe Drinking Water Act (SDWA)	Not regulated.		
FEMA Priority Substan	ces Respiratory Health	and Safety in the Flavor Manufacturing	Workplace
ISOPROPYL ALCOHO	L (CAS 67-63-0)	Low priority	
US state regulations			
5	chemicals currently listed	nt Act of 1986 (Proposition 65): This materia as carcinogens or reproductive toxins. For m	
US. California. Candida 69502.3, subd. (a))	ate Chemicals List. Safe	r Consumer Products Regulations (Cal.	Code Regs, tit. 22,
ISOPROPYL ALCOHO	L (CAS 67-63-0)		
International Inventories			
Country(s) or region	Inventory name		On inventory (yes/no)*
Australia	Australian Inventory of C	hemical Substances (AICS)	Yes
Canada	Domestic Substances List	t (DSL)	Yes
Canada	Non-Domestic Substance	s List (NDSL)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date	June-05-2013
Revision date	March-15-2019
Version #	02
Disclaimer Revision information	GFS Chemicals, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This document has undergone significant changes and should be reviewed in its entirety.