

SAFETY DATA SHEET

1. Identification

Product identifier 3-BUTEN-1-OL, 98+%

Other means of identification

Product code 3807

Recommended use professional, scientific and technical activities: scientific research and development

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name GFS Chemicals, Inc. **Address** P.O. Box 245

> Powell OH 43065 US

Telephone Phone 740-881-5501

> Toll Free 800-858-9682 Fax 740-881-5989

Website www.gfschemicals.com E-mail service@gfschemicals.com

Emergency phone Emergency Assistance

number

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3 **Health hazards** Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A

OSHA hazard(s) Not classified.

Label elements



Signal word

Hazard statement Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

> closed. Use explosion-proof electrical/ventilating/lighting equipment. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves/eye protection/face protection.

Chemtrec 800-424-9300

Response Eliminate all ignition sources if safe to do so. If on skin (or hair): Take off immediately all

> contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical

advice/attention. In case of fire: Use appropriate media for extinction.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container to an approved incineration plant.

Hazard(s) not otherwise

classified (HNOC)

Static accumulating flammable liquid

Supplemental information

Hazard statement Static accumulating flammable liquid can become electrostatically charged even in bonded and

grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and

receiving equipment. These alone may be insufficient to remove static electricity.

Material name: 3-BUTEN-1-OL, 98+% SDS US 3807 Version #: 01 Revision date: Issue date: March-25-2013 1/7

3. Composition/information on ingredients

Substances

Hazardous components

Chemical name	Common name and synonyms	CAS number	%
3-BUTEN-1-OL		627-27-0	100

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Wash off with soap and plenty of water. If skir

Irritation of eyes and mucous membranes. Irritant effects.

irritation occurs: Get medical advice/attention.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.

Most important

symptoms/effects, acute and

delaved

Indication of immediate medical attention and special

treatment needed **General information** Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Wash

contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may

be used for small fires only.

Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Do not use water jet as an extinguisher, as this will spread the fire.

This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. By heating and fire, harmful vapors/gases may be formed. Material will float and may ignite on surface of water.

Special protective equipment and precautions for firefighters

Fire-fighting

equipment/instructions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Specific methods

In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Wear appropriate personal protective equipment.

Material name: 3-BUTEN-1-OL, 98+% SDS US 3807 Version #: 01 Revision date: Issue date: March-25-2013

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk.

Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basements or confined areas.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. For waste disposal, see section 13 of the MSDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code". DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with skin. Avoid contact with eyes. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in cool place. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a well-ventilated place. Keep container tightly closed. Keep in an area equipped with sprinklers. Keep out of the reach of children. Store in a cool, dry place out of direct sunlight.

8. Exposure controls/personal protection

Occupational exposure limits No exposure limits noted for ingredient(s).

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. An eye wash and safety shower must be

available in the immediate work area.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear eye/face protection. Chemical goggles are recommended. Eye wash fountain is

recommended.

Skin protection

Hand protection Wear protective gloves.

Other Wear suitable protective clothing. Wear protective gloves.

Respiratory protection No personal respiratory protective equipment normally required. In case of insufficient ventilation,

wear suitable respiratory equipment.

Thermal hazards

General hygiene considerations

When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Keep away from food and drink, Handle in

accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance Clear. **Physical state** Liquid. Form Liquid.

> Color Colourless to light yellow.

Odor Not available.

Material name: 3-BUTEN-1-OL, 98+% SDS US 3807 Version #: 01 Revision date: Issue date: March-25-2013 3/7

Odor threshold Not available. Not available. Melting point/freezing point Not available. Initial boiling point and 233.6 °F (112 °C)

boiling range

Flash point 91.40 °F (33.00 °C)

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit -

Not available.

upper (%)

Explosive limit - lower

Not available.

(%)

Explosive limit - upper

(%)

Not available.

1.319 kPa at 25 °C Vapor pressure Vapor density Not available. **Relative density** Not available. Not available. Solubility(ies) **Partition coefficient**

(n-octanol/water)

Not available.

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Viscosity Not available.

Other information

Density 0.84 g/cm3

Flammability class Flammable IC estimated

Molecular formula C4H8O Molecular weight 72.11 Specific gravity 0.838 VOC (Weight %) 100 %

10. Stability and reactivity

Reactivity Not available.

Chemical stability Risk of ignition. Material is stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point.

Incompatible materials Oxidizing material.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Due to lack of data the classification is not possible. **Inhalation** Due to lack of data the classification is not possible.

Skin contact Not available.

Causes serious eye irritation. **Eve contact**

Symptoms related to the physical, chemical and toxicological characteristics Irritant effects.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritation Causes skin irritation.

Material name: 3-BUTEN-1-OL, 98+% SDS US 3807 Version #: 01 Revision date: Issue date: March-25-2013 4/7

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitization

Skin sensitization

Due to lack of data the classification is not possible. Due to lack of data the classification is not possible.

Germ cell mutagenicity

Due to lack of data the classification is not possible.

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicity Specific target organ toxicity

- single exposure

Due to lack of data the classification is not possible. Due to lack of data the classification is not possible.

Specific target organ toxicity

- repeated exposure

Due to lack of data the classification is not possible.

Aspiration hazard Due to lack of data the classification is not possible.

12. Ecological information

Ecotoxicity No ecotoxicity data noted for the ingredient(s).

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential Not available. **Mobility in soil** Not available. Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

> and its container must be disposed of as hazardous waste. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Not available.

Hazardous waste code

D001: Waste Flammable material with a flash point <140 F

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1993

UN proper shipping name Flammable liquids, n.o.s. (3-BUTEN-1-OL)

Transport hazard class(es) 3

Subsidary class(es) Not available.

Packing group

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Labels required

Special provisions B1, B52, IB3, T4, TP1, TP29 **Packaging exceptions** 150

Packaging non bulk 203 **Packaging bulk** 242

IATA

UN1993 **UN number**

UN proper shipping name Flammable liquid, n.o.s. (3-BUTEN-1-OL)

Transport hazard class(es) 3 Subsidary class(es) **Packaging group** TTT **Environmental hazards** No

Labels required Not available.

ERG Code 31

Special precautions for Not available.

Material name: 3-BUTEN-1-OL, 98+% 3807 Version #: 01 Revision date: Issue date: March-25-2013 5 / 7

IMDG

UN1993 **UN number**

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (3-BUTEN-1-OL)

Transport hazard class(es) 3 Subsidary class(es) **Packaging group** III **Environmental hazards**

> Marine pollutant Nο

Not available. **Labels required EmS** F-E, S-E **Special precautions for** Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations CERCLA/SARA Hazardous Substances - Not applicable.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not on regulatory list.

CERCLA Hazardous Substance List (40 CFR 302.4)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

> Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

No

SARA 311/312 No

Hazardous chemical Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Material name: 3-BUTEN-1-OL, 98+% 3807 Version #: 01 Revision date: Issue date: March-25-2013 6/7

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number**

Not listed.

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Not regulated.

DEA Exempt Chemical Mixtures Code Number

Not regulated.

Food and Drug

Not regulated.

Administration (FDA)

US state regulations California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material

is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

On inventory (yes/no)*

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Inventory name

Not regulated.

US. Pennsylvania RTK - Hazardous Substances

Not regulated.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Not listed.

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No	
Canada	Domestic Substances List (DSL)	No	
Canada	Non-Domestic Substances List (NDSL)	Yes	
China	Inventory of Existing Chemical Substances in China (IECSC)	No	
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes	
Europe	European List of Notified Chemical Substances (ELINCS)	No	
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes	
Korea	Existing Chemicals List (ECL)	Yes	
New Zealand	New Zealand Inventory	Yes	
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No	
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes	
*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)			

16. Other information, including date of preparation or last revision

Issue date March-25-2013

Version # 01

Further information Not available.

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

> available. The information given is designed only as a quidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

in the text.

Revision Information Hazards Identification: US Hazard Categories

Physical & Chemical Properties: Multiple Properties Regulatory Information: Risk Phrases - Class.

GHS: Classification

Material name: 3-BUTEN-1-OL, 98+% SDS US 3807 Version #: 01 Revision date: Issue date: March-25-2013 7/7